

Enhance Your Business

ELLIX 35/ELLIX 45

High Quality Thermal Receipt Printer

User-Friendly Elegant Design
Powerful and Reliable System Architecture


- Paper Jam-Free Auto Cutter
- Fast Printing Speed
- Comprehensive Barcode Formats
- Low Power Consumption and Paper Saving
- Supports Various Options and Interfaces



Easy Paper Loading
Auto Cutter



Many Interface Options




Reliable Metal Frame
Structure with Low Noise



Easy Assembly and
Disassembly



Automatic Display
Pivot Function for
Wall Mounting



ELLIX 35/ELLIX 45

Multifunction Printer for ECR & POS

Stylish Design

- Modern color and design

Reliable System

- Fast printing speed of max 220mm/sec
- Support various barcodes
- Low power consumption and paper saving

Various Interfaces

- Combo interfaces(Ethernet+RS-232+USB)
- Variety of interface options(Ethernet, Wi-Fi, Bluetooth, etc.)
- USB default

User-Friendly Features

- LCD display panel option(ELLIX45)
- Paper jam-free feature
- Firmware downloadable using a USB stick
- Tool-free cabinet for easy assembly and disassembly



ELLIX 35/ELLIX 45 have a modern and compact design and meet the needs of demanding hospitality and retail environments.



Items		ELLIX 35	ELLIX 45
Printing method		Direct thermal line printing	
Printing speed	Mono paper 80mm	Max. 180mm/sec(43 line/sec)	Max. 220mm/sec(52 line/sec)
	Mono paper 58mm	Max. 150mm/sec(36 line/sec)	Max. 150mm/sec(36 line/sec)
	Two color paper	Max. 100mm/sec(24 line/sec)	
Printing resolution		180 dpi	
Printing width	Mono paper 80mm	Max. 72.0mm	
	Mono paper 58mm	48mm(Max. 54mm)	
Paper	Loading	Drop-in type	
	Dimension	Max. 58.0/80,0 x Φ83,0mm	
	Thickness	0.06~0.08mm	
Auto cutter		Guillotine type(Jam-free)	
Memory	PGM memory	2 Mbyte	10 Mbyte
	Data memory	8 Mbyte	
	Data buffer	Max. 64 KB	
Reliability	Mechanism(MCBF)	70,000,000 lines	
	TPH	1x10 ⁶ Pulse, 150 Km	
	Auto cutter	1,500,000 cut	
Bar code		UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF, CODABAR, PDF417, QR code	
Driver		Windows Driver, OPOS Driver	
Drawer port		2 Ports(+24V)	
Interface		USB+RS-232, USB+Parallel, USB+WLAN(Wi-Fi), USB+Ethernet+RS-232	USB Only, USB+RS-232, USB+Parallel, USB+Ethernet, USB+WLAN(Wi-Fi), USB+Bluetooth, USB+Ethernet+RS-232
Power supply(SMPS Adapter)		IN: AC 90~264V, OUT: DC 24V 2.5A	
Option	Wall mount kit	Yes	
	Paper separator(58.0mm)	Yes	
	Kitchen bell	Yes	
	LCD display	No	Yes
	Near end sensor	Yes	Default
	Black mark sensor	Yes	
	Splash cover	Yes	